

Power Universal Pink Control Indikator

Resin-reinforced adhesive with pleasant lemon aroma and pink control to make an evenly applying easier to the wallpaper.

Instructions for use: *Power Universal Pink Control Indikator* is ideally suitable for pasting light and heavy woodchip wallpapers, paper wallpapers and vinyl wallpapers on mineral surfaces and gypsum boards

Technical specifications:

Components:	Starch ether, poly vinyl acetate powder
Density:	approx. 0.3-0.4g/cm ³
pH-value:	approx. 8-9
Solubility:	Ready for use after approx. 5 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *decotric Wallpaper Remover*. Make good cracks and holes using *decotric Interior* or *decomur Super Bonding Filler*. Pretreat highly absorbent, sanding and chalking surfaces using *decotric Deeply Penetrating Primer – Solvent Free*.

Application: Stirring vigorously, sprinkle *Power Universal Pink Control Indikator* into clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. The prepared adhesive with a pleasant lemon aroma is pink coloured to the make an evenly applying to the wallpaper easier.

Paste wallpaper evenly with *Power Universal Pink Control Indikator* and fold over. After sufficient softening, apply on impact and press on.
After dryness the adhesive is transparent.

Always observe the wallpaper manufacturer's instructions for use.

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 250-g packet	Coverage of a 250-g packet
pre-pasting/ priming	1:40	10 l	40-44 m ²
heavyweight wallpapers and reinforcing fabrics	1:20	5 l	25-30 m ² 5-7 rolls
light paperbacked wallpapers	1:30	7,5 l	ca. 35 m ² ca. 7 rolls

Storage: Store in a cool and dry place!

Available size: 250 g collapsible box 022405026

Shelf life: Min. 5 years as of production date.
Date of manufacture – see print